

3M™ Scotchgard™ Multi-Layer Protective Film

1004

Technical Data

September, 2014

Product Description 3M™ Scotchgard™ Multi-Layer Protective Films 1004 is an optically transparent, pressure-sensitive polyester film tapes designed to protect surfaces from intentional and unintentional damage caused by scratching, etching, abrasion and graffiti. A damaged film layer can be quickly and easily removed, exposing a fresh protective sheet.

Product Construction	Backing	Adhesive	Sizes
	Polyester	Acrylic	Sheets and Custom Sizes

Typical Physical Properties **Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.**

	1004	ASTM Test Method
Number of Layers:	4	
Film Thickness:	19.5 mils (0.5 mm)	D-3652
Base Layer Adhesion to Glass:	23 oz./in. (25 N/100 mm)	D-3330
Layer-to-Layer Adhesion:	11 oz./in. (12 N/100 mm)	D-3330
Visible Light Transmission:	90%	D-1003
Haze:	3%	D-1003
Clarity:	98%	D-1003

- Features**
- Multi-layer construction reduces total application and removal costs versus single layer protection.
 - Thick polyester film construction prevents typical scratches from affecting layers below.
 - Film protects glass from chemical etching agents such as Bath Etch™ or Armour Etch™.
 - Film on glass meets ASTM E162, ASTM E662, FMVSS-302 and Bombardier SMP 800-C requirements.
 - Durable top-coat layer prevents light scratches caused by installation, wiping, cleaning or abrasion.
 - Optimized adhesive provides easy, clean removal from glass and most other surfaces.
 - Optimized inter-layer adhesive provides firm, adequate adhesion yet fast and easy removal.
 - High clarity construction provides glass-like appearance.

3M™ Scotchgard™ Multi-Layer Protective Film

1004

Applications

3M™ Scotchgard™ Multi-Layer Protective Films 1004 protects glass, metal and other surfaces that are subject to damage from scratching, cutting, abrasion or chemical etching. Used for protecting smooth, flat surfaces such as public transportation windows and doors, transit kiosks, shelters, displays, mirrors and elevators.



Application Techniques

- For best results, surface must be clean and free of dirt, debris and oils and should be applied when surface temperature exceeds 50°F (10°C).
- Use of an application solution and 3M Heavy Duty Squeegee is suggested for easy positioning and squeegee application.
- Removal of film layers immediately after wet application is not recommended.
- Use of film removal tool is recommended for easy peel-back of target layer.
- For detailed Application Instructions and Tips, see 3M Technical Bulletin (70-0709-5334-7).

Application Information

- Some acrylic and polycarbonate substrates have low surface energy coatings and/or may out-gas, leading to bubbling or adhesion issues. Test before use.
- Not approved as glazing material for windshields requiring conformance to Federal Code 49 CFR 571.205. This standard applies to passenger cars, multi-purpose passenger vehicles, trucks, buses, motorcycles, slide-in campers and pick-up covers.
- May be used outdoors for short term use (typically <1 year) with minimal change in haze, clarity, light transmission and minimal adhesive residue left on most surfaces. Some exposure conditions (e.g. direct sun facing, higher temperatures) may shorten performance.
- Blocks more than 98% of UV light that can degrade plastics and fabrics.
- **Note:** Removal of film layer generates static charge.

Storage

Store flat under normal conditions of 60° to 80°F (16° to 27°C) and 40 to 60% R.H. in the original carton.

Shelf Life

To obtain best performance, use this product within 24 months from date of manufacture.

3M™ Scotchgard™ Multi-Layer Protective Film

1004

Technical Information

The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Product Use

Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Warranty, Limited Remedy, and Disclaimer

Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability

Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

ISO 9001:2008

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001:2008 standards.



Industrial Adhesives and Tapes Division

3M Center, Building 225-3S-06
St. Paul, MN 55144-1000
800-362-3550 • 877-369-2923 (Fax)
www.3M.com/industrial



Recycled Paper
40% pre-consumer
10% post-consumer

3M and Scotchgard are trademarks of 3M.
Bath Etch and Armour Etch are trademarks
of Armour Products, Wyckoff, NJ.
Printed in U.S.A.
©3M 2014 70070953339 (9/14)